

DOCKSIDE MOORING BOLLARD

DOCKSIDE BOLLARD – DT TYPE

Product Code : AE-1020

Model	Dimension (mm)						No. of Bolts	Pull Load (Ton)
	A	B	C	D	E	F		
DT 20	460	380	460	230	300	60	6 X 24	20
DT 30	460	380	460	230	300	60	6 X 36	30
DT 50	700	590	690	340	450	80	8 X 42	50
DT 75	900	800	900	450	600	100	8 X 48	75
DT 100	900	800	900	450	600	100	8 X 52	100
DT 150	1060	850	1060	560	800	120	8 X 64	150
DT 200	1060	850	1060	560	800	120	8 X 72	200
DT 250	1060	850	1060	560	800	120	8 X 76	250

- Remark: 1. MBL of Bollard = 3 x Pull Load; Proof Load = 1.5 x Pull Load.
 2. Can be supplied in cast iron, spheroidal graphite iron and cast steel to International Standards.
 3. Supplied with a hole in the top to facilitate filling with grout and would be recommend this practice.
 4. Use of break off bolts has been introduced for Bollard anchorage and whilst increasing the cost of anchorage system, more advantages when usage.
 5. Operating at angles from horizontal to 60° above, and are if 180° with 3 safety factor.
 6. Installation drawing available as request.

